

isolera inside corner FDB professional

Highly elastic moulding made of rubber with special fleece coating on both sides for permanent sealing of internal corners in combination with sealing systems under ceramic coverings.

Characteristics:

Waterproof and permanently elastic inner corner made of rubber reinforced with protruding special fleece. The protruding fleece and the good adhesive properties of the special rubber create an excellent bond with the isolera waterproofing materials under tiles.

Fields of application:

For permanent watertight sealing of corners under ceramic coverings in bonded waterproof membranes. For all moisture stress classes. For use in composite waterproofing on balconies, loggias and arcades according to DIN 18531, in interior rooms according to DIN 18534 as well as in tanks and basins according to DIN 18535. Resistance table available.

Technical data:

Colour:	grey
Temperature resistance:	-20°C to +90°
Thickness:	C 0.6 mm
Leg length:	100 mm

Preparation of the substrate:

The substrate preparation depends on the substrate to be coated, the substrate condition and the intended waterproofing system. It is strongly recommended to apply an isolera primer. After the primer has dried, the area in which the inside corner is to be used is coated with isolera Elastogum Plus or isolera Elastschlämme 1K Plus or 2K.

Processing:

The corner is placed in the freshly applied coating and pressed on. During the second coating with the sealing compound, the complete corner is integrated into the system.

Notes for follow-up work:

The corner is silicone-compatible, there is no risk of bleeding through. Thin-bed mortar and coatings can be applied directly in the bond. Before applying further products, it is recommended to carry out a compatibility test.

Cleaning of the tools:

Clean tools and dirty areas with water immediately after use.

Storage:

Can be stored in a cool, dry place in the original packaging for 24 months.

Delivery form:

25 pieces / carton

Hazard statements:

Not a hazardous substance as defined by the Ordinance on Hazardous Substances.

Further information can be found in the safety data sheet.



isolera BAU &
ABDICHTUNGS
SYSTEME

isolera GmbH | Gamsweg 17 | 36041 Fulda |
www.isolera.de Tel. +49 (0) 661.250 94 83