isolera WALL SLEEVE FDB flex

Highly elastic sealing sleeve made of rubber with knitted reinforcement for sealing pipe penetrations in combination with sealing systems under ceramic coverings.

Characteristics:

Waterproof, permanently elastic sealing sleeve made of special rubber with a knitted insert in the centre. This material combination results in an excellent bond with all sealing materials used under tiles, such as polymer dispersions and mineral elastic sealing slurries as well as reaction resin sealants.

Fields of application:

As a permanent waterproof seal in the wall area for pipe penetrations on shower and bathtub fittings under ceramic coverings. Use in bonded waterproofing on balconies, loggias and arcades according to DIN 18531 as well as indoors according to DIN 18534.

Technical specifications:

Colour: grey

Strength: approx. 0.62 mm
Temperature resistance: -20°C to +90°C

Preparation of the substrate:

The substrate preparation depends on the substrate to be coated, the substrate condition and the intended waterproofing system. It is strongly recommended to apply an isolera primer. After the primer has dried, the area in which the sleeve is to be used is coated with isolera Elastogum Plus or isolera Elastschlämme 1K Plus or 2K.

Processing:

The sleeve is inserted into the freshly applied coating and pressed on. During the second coating with the sealing compound, the complete sleeve is integrated into the system.

Notes for follow-up work:

The sleeve is silicone-compatible, there is no risk of bleeding through. Thin-bed mortar and coatings can be applied directly in the bond. Before applying other products, it is recommended to carry out a compatibility test.

Cleaning of the tools:

Clean tools and dirty areas with water immediately after use.

Storage:

Can be stored for 24 months in a cool, dry place in the original packaging.

Delivery form:

25 piece / carton

Dimension:

120 x 120 mm

Hazard statements:

Not a hazardous substance as defined by the Ordinance on Hazardous Substances.

