

# isolera BUTYL SEALING TAPE SK

Self-adhesive, fleece-coated sealing tape for permanently elastic joint sealing under ceramic coverings



## Properties:

Fleece-coated, alkali-resistant, permanently elastic butyl sealing tape with high adhesive and tear resistance. The fleece coating enables an excellent bond with all sealing materials used under tiles, such as polymer dispersions, mineral, flexible sealing slurries and reaction resin seals.

## Areas of application:

For corner formation and for bridging joints in bonded waterproofing. For all moisture exposure classes. For use in bonded waterproofing on balconies, loggias and arcades in accordance with DIN 18531 and interiors in accordance with DIN 18534. For secure sealing of membrane joints of membrane waterproofing in accordance with PG AIV-B in the area of fleece-free edges up to W2-I in accordance with DIN 18534-5 and W3-I as a special construction. Bonding of waterproofing to plastic, wood and metal surfaces.

## Technical data:

Processing temperature:	ab +5°C
Material thickness width 100 mm:	ca. 0,7 mm
Material thickness Width 250 mm:	ca. 0,8 mm

## Preparation of the substrate:

Depending on the type and condition of the substrate and the intended sealing system, the substrate must be prepared. Apply a suitable primer for this purpose. Once the primer has dried, apply the sealing tape directly to the substrate.

## Processing:

Cut the sealing tape to the required length. Peel off the silicone film on the back of the sealing tape and press firmly onto the intended surface. The sealing tape must be positioned correctly when it is first applied. Subsequent correction is only possible to a limited extent, depending on the substrate. For safety reasons, the sealing tape should then be replaced with a new section.

## Consumption:

Allow for an overlap of at least 5 cm.

## Notes for follow-up work:

Excellent compatibility and a good bond with polymer dispersions, mineral flexible sealing slurries and reactive resins is guaranteed. A compatibility test should be carried out before applying other products.

## Cleaning the tools:

Clean tools and soiled areas with water immediately after use.

## Storage:

Shelf life 24 months at room temperature, protected from direct sunlight and stored in a dry place.

## Delivery form:

Width: 100 mm	Width: 250 mm
Roll á 25 m	Roll á 10 m
1 roll / carton	1 roll / carton

## Hazard warnings:

Not a hazardous substance in the sense of the Hazardous Substances Ordinance.

## Disposal:

Leftovers and packaging can be disposed of through the Green Dot via the Dual System Germany.

	<b>isolera</b> BAU & ABDICHTUNGS SYSTEME
isolera GmbH   Gamsweg 17   36041 Fulda   www.isolera.de Tel. +49 (0) 661.250 94 83	