

SEALING TAPE, FLEECECOATED SK

Self-adhesive, fleece-coated sealing tape for sealing expansion joints



Properties:

Elastic sealing tape based on NBR rubber with good resilience. The fleece coating on both sides ensures excellent adhesion with bitumen thick coatings and flexible mineral sealing slurries. It is also possible to bond the sealing tape with solvent-free, flexible reactive resins.

Areas of application:

Attachment and integration of liquid waterproofing materials to non-mineral building materials and connection areas such as plastic, metal and wood.

Technical data:

Temperature resistance:	-20 °C to +90 °C
Thickness of sealing tape:	0,9 mm
Width of sealing tape:	250 mm
Width of adhesive strip:	30 mm

Preparation of the substrate:

The substrate must be firm, stable and largely level. Soiling from oil, grease, dust or other separating agents must be removed. Gravel pockets and cavities as well as unevenness must be levelled out with suitable products. A suitable isolera primer must be applied to the substrate to be sealed.

Processing:

Cut the sealing tape to the required length. Remove the silicone film from the adhesive strip and fix it to the prepared substrate. Then lay the sealing tape into the freshly applied sealing product. Any unevenness can be pressed down with a smoothing trowel.

Consumption:

Allow for an overlap of at least 5 cm.

Notes for follow-up work:

Solvent-free adhesives and coatings can be applied directly.

Cleaning the tools:

Clean tools with water immediately after use.

Storage:

Can be stored indefinitely at room temperature, protected from direct sunlight and in a dry place.

Delivery form:

Width: 250 mm
Roll á 25 m
1 roll / carton

Hazard warnings:

Not a hazardous substance in the sense of the Hazardous Substances Ordinance.

Disposal:

Leftovers and packaging can be disposed of through the Green Dot via the Dual System Germany.

	isolera BAU & ABDICHTUNGS SYSTEME
isolera GmbH Gamsweg 17 36041 Fulda www.isolera.de Tel. +49 (0) 661.250 94 83	